

ATM



*Desktop equipment
ideal for the service
and healthcare sectors.*



Most used sectors



INDUSRTY



ELECTRONICS



AUTOMOTIVE



JEWELRY



SANITARY



OPTICS



LAB



DENTAL

Advantages

ASEPSIS GUARANTEED

NO DAMAGE TO THE PARTS

DEEP AND UNIFORM CLEANING

SPEED AND EFFICIENCY

EASY TO USE

Equipment designed to remove residue from **delicate instruments and parts**, ensuring optimal hygiene without damaging materials.

Their **manageable size and high efficiency** make them a versatile solution for environments requiring both precise and gentle cleaning.



ATM 1L

220V - 160 W - 0,7 A
I.V. 159 x 135 x 60 mm



ATM 2L

220V - 170 W - 0,8 A
I.V. 159 x 135 x 100 mm



ATM 3L

220V - 220 W - 1 A
I.V. 240 x 135 x 100 mm



ATM 6L

220V - 380 W - 1,7 A
I.V. 300 x 150 x 150 mm



ATM 10L

220V - 540 W - 2,5 A
I.V. 300 x 240 x 150 mm



ATM 20L

220V - 880 W - 4 A
I.V. 495 x 295 x 150 mm



ATM 30L

220V - 1100 W - 5 A
I.V. 495 x 295 x 200 mm

All units include:

- Lid
- Basket
- Power cable
- Manual + CE



ATM 1L

ELECTRICAL SPECIFICATIONS

Voltage	220/230 V - 50/60 Hz
Power	160 W
Ultrasonic power	60 W (120W p-p)
Heating power	100 W
Amperage	0,7 A

OPERATING SPECIFICATIONS

Frequency	40 KHz Sweep System $\pm 2\%$
Temperature selection	0 - 80°C
Timer	0 - 600s

FINISHES AND ACCESORIES

- Cuba, casing, lid and basket in AISI 304 Stainless Steel
 - Noise-reducing lid
 - Basket with handles (maya 10mm)
- Digital display for temperature and timer selection
- High-strength buttons under 3mm protective vinyl
- Includes Manual + CE

DIMENSIONS

INTERNAL (mm)

LENGTH	WIDTH	HEIGHT
159	135	60

* Useful work volume

EXTERNAL (mm)

LENGTH	WIDTH	HEIGHT
200	170	220

*External dimensions with handle and valve

WEIGHT

- Weight: 2,3 kg
- Weight + packaging: 2,8 kg
- Packaging dimensions: 350 x 235 x 270 mm



EMC, LVC Y RoHS Directives:

2014/30/EU - 2014/34/EU - 2011/65/EU

Based on the tests carried out under normal operating conditions on the representative sample of the aforementioned model, the following certificates are created:

BCTC-151113890 / BCTC-151113891 / BCTC-FYC170102352C / BCTC-FYC170102352



ATM 2L

ELECTRICAL SPECIFICATIONS

Voltage	220/230 V - 50/60 Hz
Power	170 W
Ultrasonic power	70 W (140W p-p)
Heating power	100 W
Amperage	0,8 A

OPERATING SPECIFICATIONS

Frequency	40 KHz Sweep System $\pm 2\%$
Temperature selection	0 - 80°C
Timer	0 - 600s

FINISHES AND ACCESORIES

- Cuba, casing, lid and basket in AISI 304 Stainless Steel
 - Noise-reducing lid
 - Basket with handles (maya 10mm)
- Digital display for temperature and timer selection
- High-strength buttons under 3mm protective vinyl
- Includes Manual + CE

DIMENSIONS

INTERNAL (mm)

LENGTH	WIDTH	HEIGHT
159	135	100

* Useful work volume

EXTERNAL (mm)

LENGTH	WIDTH	HEIGHT
200	170	220

*External dimensions with handle and valve

WEIGHT

- Weight: 2,4 kg
- Weight + packaging: 2,9 kg
- Packaging dimensions: 350 x 235 x 270 mm



EMC, LVC Y RoHS Directives:

2014/30/EU - 2014/34/EU - 2011/65/EU

Based on the tests carried out under normal operating conditions on the representative sample of the aforementioned model, the following certificates are created:

BCTC-151113890 / BCTC-151113891 / BCTC-FYC170102352C / BCTC-FYC170102352



ATM 3L

ELECTRICAL SPECIFICATIONS

Voltage	220/230 V - 50/60 Hz
Power	220 W
Ultrasonic power	120 W (240W p-p)
Heating power	100 W
Amperage	1 A

OPERATING SPECIFICATIONS

Frequency	40 KHz Sweep System $\pm 2\%$
Temperature selection	0 - 80°C
Timer	1 - 99m
Ultrasonic Potentiometer	0 - 100%

FINISHES AND ACCESORIES

- Cuba, casing, lid and basket in AISI 304 Stainless Steel
 - Noise-reducing lid
 - Basket with handles (maya 10mm)
- Digital display for temperature and timer selection
- High-strength buttons under 3mm protective vinyl
- ½" drain valve with female end + grate
- Includes Manual + CE

DIMENSIONS

INTERNAL (mm)

LENGTH	WIDTH	HEIGHT
240	135	100

* Useful work volume

EXTERNAL (mm)

LENGTH	WIDTH	HEIGHT
300	200	300

*External dimensions with handle and valve

OTHERS

- Weight: 3,9 kg
- Weight + packaging: 4,7 kg
- Packaging dimensions: 345 x 250 x 360 mm



EMC, LVC Y RoHS Directives:

2014/30/EU - 2014/34/EU - 2011/65/EU

Based on the tests carried out under normal operating conditions on the representative sample of the aforementioned model, the following certificates are created:

BCTC-151113890 / BCTC-151113891 / BCTC-FYC170102352C / BCTC-FYC170102352



ATM 6L

ELECTRICAL SPECIFICATIONS

Voltage	220/230 V - 50/60 Hz
Power	380 W
Ultrasonic power	180 W (360W p-p)
Heating power	200 W
Amperage	1,7 A

OPERATING SPECIFICATIONS

Frequency	40 KHz Sweep System $\pm 2\%$
Temperature selection	0 - 80°C
Timer	1 - 99m
Ultrasonic Potentiometer	0 - 100%

FINISHES AND ACCESORIES

- Cuba, casing, lid and basket in AISI 304 Stainless Steel
 - Noise-reducing lid
 - Basket with handles (maya 10mm)
- Digital display for temperature and timer selection
- High-strength buttons under 3mm protective vinyl
- ½" drain valve with female end + grate
- Includes Manual + CE

DIMENSIONS

INTERNAL (mm)

LENGTH	WIDTH	HEIGHT
300	150	150

* Useful work volume

EXTERNAL (mm)

LENGTH	WIDTH	HEIGHT
360	210	300

*External dimensions with handle and valve

OTHERS

- Weight: 5,1 kg
- Weight + packaging: 6 kg
- Packaging dimensions: 400 x 260 x 365 mm



EMC, LVC Y RoHS Directives:

2014/30/EU - 2014/34/EU - 2011/65/EU

Based on the tests carried out under normal operating conditions on the representative sample of the aforementioned model, the following certificates are created:

BCTC-151113890 / BCTC-151113891 / BCTC-FYC170102352C / BCTC-FYC170102352



ATM 10L

ELECTRICAL SPECIFICATIONS

Voltage	220/230 V - 50/60 Hz
Power	540 W
Ultrasonic power	240 W (480W p-p)
Heating power	300 W
Amperage	2,5 A

OPERATING SPECIFICATIONS

Frequency	40 KHz Sweep System $\pm 2\%$
Temperature selection	0 - 80°C
Timer	1 - 99m
Ultrasonic Potentiometer	0 - 100%

FINISHES AND ACCESORIES

- Cuba, casing, lid and basket in AISI 304 Stainless Steel
 - Noise-reducing lid
 - Basket with handles (maya 10mm)
- Digital display for temperature and timer selection
- High-strength buttons under 3mm protective vinyl
- ½" drain valve with female end + grate
- Includes Manual + CE

DIMENSIONS

INTERNAL (mm)

LENGTH	WIDTH	HEIGHT
300	240	150

* Useful work volume

EXTERNAL (mm)

LENGTH	WIDTH	HEIGHT
400	300	300

*External dimensions with handle and valve

OTHERS

- Weight: 6,9 kg
- Weight + packaging: 8,5 kg
- Packaging dimensions: 425 x 365 x 380 mm



EMC, LVC Y RoHS Directives:
2014/30/EU - 2014/34/EU - 2011/65/EU
 Based on the tests carried out under normal operating conditions on the representative sample of the aforementioned model, the following certificates are created:
BCTC-151113890 / BCTC-151113891 / BCTC-FYC170102352C / BCTC-FYC170102352



ATM 20L

ELECTRICAL SPECIFICATIONS

Voltage	220/230 V - 50/60 Hz
Power	880 W
Ultrasonic power	480 W (960W p-p)
Heating power	400 W
Amperage	4 A

OPERATING SPECIFICATIONS

Frequency	40 KHz Sweep System $\pm 2\%$
Temperature selection	0 - 80°C
Timer	1 - 99m
Ultrasonic Potentiometer	0 - 100%

FINISHES AND ACCESORIES

- Cuba, casing, lid and basket in AISI 304 Stainless Steel
 - Noise-reducing lid
 - Basket with handles (maya 10mm)
- Digital display for temperature and timer selection
- High-strength buttons under 3mm protective vinyl
- ½" drain valve with female end + grate
- Includes Manual + CE

DIMENSIONS

INTERNAL (mm)

LENGTH	WIDTH	HEIGHT
495	295	150

* Useful work volume

EXTERNAL (mm)

LENGTH	WIDTH	HEIGHT
600	360	320

*External dimensions with handle and valve

OTHERS

- Weight: 11,4 kg
- Weight + packaging: 14,1 kg
- Packaging dimensions: 660 x 455 x 440 mm



EMC, LVC Y RoHS Directives:

2014/30/EU - 2014/34/EU - 2011/65/EU

Based on the tests carried out under normal operating conditions on the representative sample of the aforementioned model, the following certificates are created:

BCTC-151113890 / BCTC-151113891 / BCTC-FYC170102352C / BCTC-FYC170102352



ATM 30L

ELECTRICAL SPECIFICATIONS

Voltage	220/230 V - 50/60 Hz
Power	1100 W
Ultrasonic power	600 W (1200W p-p)
Heating power	500 W
Amperage	5 A

OPERATING SPECIFICATIONS

Frequency	40 KHz Sweep System $\pm 2\%$
Temperature selection	0 - 80°C
Timer	1 - 99m
Ultrasonic Potentiometer	0 - 100%

FINISHES AND ACCESORIES

- Cuba, casing, lid and basket in AISI 304 Stainless Steel
 - Noise-reducing lid
 - Basket with handles (maya 10mm)
- Digital display for temperature and timer selection
- High-strength buttons under 3mm protective vinyl
- ½" drain valve with female end + grate
- Includes Manual + CE

DIMENSIONS

INTERNAL (mm)

LENGTH	WIDTH	HEIGHT
495	295	200

* Useful work volume

EXTERNAL (mm)

LENGTH	WIDTH	HEIGHT
600	360	390

*External dimensions with handle and valve

OTHERS

- Weight: 13 kg
- Weight + packaging: 15,8 kg
- Packaging dimensions: 660 x 455 x 485 mm



EMC, LVC Y RoHS Directives:

2014/30/EU - 2014/34/EU - 2011/65/EU

Based on the tests carried out under normal operating conditions on the representative sample of the aforementioned model, the following certificates are created:

BCTC-151113890 / BCTC-151113891 / BCTC-FYC170102352C / BCTC-FYC170102352



OTHER SERVICES



Chemical Products



Maintenance Department

Aplicaciones Técnicas por Ultrasonidos S.L.
- *Technical Applications by Ultrasound* -
All rights reserved

CONTACT US

COMMERCIAL

 (34) 649 913 355

 jam@ultrasonidosatu.com

ADMINISTRATION

 (34) 963 753 712

 montse.vidal@ultrasonidosatu.com

C/Algepser 22 Nave 8, Paterna, Valencia, Spain

@atu_maquinas_ultrasonidos

www.ultrasonidosatu.com